

Heavy Metal Field Gates

A heavy duty gate is essential for any farm, field or agricultural settings. Our high quality heavy metal field entrance gates are available in a range of designs and sizes. We offer a selection of two styles of metal field gates available singularly or in pairs with a choice of drop bolts. They arrive in a galvanised finish.



The top and bottom rails are 41.5mm tube, with middle rails which are 32mm tube.



Specification: Gates are 1.15m high. Hanging stile of 50mm x 25mm box section. Slam stile of 50mm x 25mm box section. Top and bottom rails 41.5mm tube, with middle rails 32mm tube. Fittings include adjustable hinges and padlockable sliding latch. Also available with welded mesh cladding, (600mm high x 50mm x 50mm x 4mm) to the bottom part of the gate, please see below.

Heavy Metal Field Gates

Length	Standard Un-clad Ref	Clad with Wire Mesh Ref
1.20m	440800 ○	440880BM ●
2.10m	441100 ○	441110BM ●
2.40m	441200 ○	441220BM ●
2.70m	441300 ○	441330BM ●
3.00m	440200 ●	440220BM ●
3.30m	440300 ●	440330BM ●
3.60m	440400 ●	440440BM ●
4.20m	440500 ●	440550BM ●
4.60m	440600 ●	440660BM ●

Welded mesh should normally be clad to inside of the gate with bracing on outside to avoid animals climbing up the rails. Please also note: Any metal field gate clad with mesh should be hung on 114mm diameter posts.

Drop Bolts and Loop Over Catches

Description	Ref
Drop bolt	453880 ●
Loop over catch	453700 ●

Drop bolts and loop over catches are available for self fitting if pairs are required.



Excellent quality fence. Helpful and friendly staff.
Delivered on time. Can't really ask for more!

Phill Nicholls, October 2023

Hanging Posts

Description	Ref
1.875m long x 89mm Diameter	453200 ●
1.875m long x 114mm Diameter	453100 ●

89mm diameter posts should be used up to 3.30m wide 114mm diameter posts should be used on 3.30m wide and above.

Slam Posts

Description	Ref
1.80m long 88.9mm Diameter	453600 ●

● Stock items ○ Made to order (cannot be cancelled once ordered)



Due to the erratic price changes in raw material, we have temporarily removed prices from our Good Fencing Guide.

To see our latest prices, view our Heavy Metal Field Gates on our website by scanning the QR code.

Estate Railings & Gates

Estate fencing has a classic style that everyone associates with country parks and rural estates.

Our traditional estate fencing is ideal for use as a continuous boundary fence in parkland, paddocks, deer parks, estates or estate grounds. The fencing is constructed from steel and is galvanised as standard. Our fencing and gates can be powder coated to your choice of colour.



Our Estate Fencing is ideal for use on uneven ground as it follows the contours of the ground and can easily be stepped. Please note: panels can only be stepped, not raked. Images show optional black PPC finish.



We have improved the traditional fence design and created an economical, modern, tubular version that is stronger, lighter and virtually maintenance free. All of our steel fencing is galvanised and has a 25 year service life guarantee.

Metal Estate Railing Fencing

Description	Ref
Panel 2.00m wide overall x 1.20m high above finished ground level. End posts/uprights 50mm x 25mm RHS (end posts are drilled with 2 holes for bolting to the next panel). Product is galvanised as standard and PPC black is an optional extra.	079800 ○
End post for cut back panel	079801 ○
M8 x 65 Coach Bolt (2 per panel)	804100 ○
M8 washers	073304 ○

Estate Railing Gates

Manufactured from the same high quality materials and with all the same benefits as the Estate Railings, this elegant gate is ideal for use with railings or in the place of any metal field gate. The graceful crook with the diagonal strengthening brace adds an attractive feature.

Any metal field gate clad with mesh should be hung on 114mm diameter posts.

Estate Railing Gates

Description	Ref
1.20m wide	079400BM ○
3.00m wide	079500BM ○
3.60m wide	079600BM ○

Galvanised as standard, powder coating available as an option - please ask. Posts are filled with heavy duty black plastic infills, for all colours including galvanised.

○ Made to order (cannot be cancelled once ordered)



Due to the erratic price changes in raw material, we have temporarily removed prices from our Good Fencing Guide.

To see our latest prices, view Estate Railings and Gates on our website by scanning the QR code.

Post & Rail Special Heavy Morticed

This attractive design will appeal to those who want a timeless, traditional or agricultural style fencing with a rustic feel.



Comprising of half round vertical posts, with either three or four mortices, for the irregular sawn horizontal rails to insert into.



Allow one post for every 1.85m of fence, plus one for the end of the run.

For a 3-rail fence allow three rails per 1.85m and for a 4-rail fence, also allow four rails per 1.85m. All timber used throughout is superior quality Jakcure® treated softwood guaranteed for 25 years. The posts have a galvanised gangnail embedded in top to reduce splitting.

Posts

Peeled half round softwood Jakcure® treated with a minimum of 125mm across the face. (Mortices 100 x 40mm are centred at 125mm, 500mm, 850mm, 1150mm from the top of the post).

Length	Ref

Rails

Irregular sawn sections of softwood Jakcure® with a minimum girth of 250mm peeled, with ends tapered to fit mortices.

Length	Ref



Handy Tip

After dividing the length of the fence run by the post intervals, always add one extra post to complete the run. Remember, corner posts take the place of ordinary posts. Aids for erecting posts - Shuv-holer and Monkey Hole Borer - see page 158.

Corner Posts

Peeled round, softwood Jakcure® treated with a minimum diameter of 125mm. Morticed two ways. (Mortices 100mm x 40mm are centred at 125mm, 500mm, 850mm, 1150mm from the top of the post).

Length	Ref

Nails

Description	Ref
1kg bag of 50mm Stainless Steel Nails	800710 ●
5kg box of 50mm Stainless Steel Nails	800750 ●

2kgs required for 180m of 3-rail fence. 3kgs required for 180m of 4-rail fence (441 nails approx. per kg).

- Stock items ○ Made to order (cannot be cancelled once ordered)
- Check for availability



Due to the erratic price changes in raw material, we have temporarily removed prices from our Good Fencing Guide.

To see our latest prices, view our Post & Rail Special Heavy Morticed page on our website by scanning the QR code.

Post & Rail Nailed

This highly durable and versatile fencing comprises of machine rounded half round vertical posts, with three horizontal machine rounded half round rails nailed to the flat face of the posts.



Due to the erratic price changes in raw material, we have temporarily removed prices from our Good Fencing Guide.

To see our latest prices, view our Post & Rail Nailed on our website by scanning the QR code.

Post and Rail Nailed fencing is a robust agricultural style system which can have 2, 3, or 4 rails depending on what is required.



Square Post & Rail Fencing

Allow one post for every 1.80m of fence, plus one for the end of the run. This traditional versatile fencing consists of machine rounded half round posts, with three horizontal machine rounded half round rails, nailed to the flat face of the square posts.

Allow three rails for every 3.60m of 3-rail fencing.

All timber used throughout is superior quality Jakcure® treated softwood guaranteed for 25 years.

Recommendation: When erecting post and rail fencing in the Summer it is advisable to set posts in concrete as it is very difficult or impossible to ram dry soil tight.

Machine Rounded, Half Round Posts

Description	Ref
1.80m 125mm face	150110 ●
2.40m 125mm face	131300 ●

(2.40m posts are recommended for use in soft ground or a 1.50m high fence).

Machine Rounded, Corner Posts

Jakcure® treated softwood with two sawn flat sides from round post of 125mm diameter.

Length	Ref
1.80m	130550 ●

Half Round Rails

Machine rounded half round Jakcure® treated rails.

Description	Ref
3.60m long with 100mm face	135000 ●



We purchased a post and rail fence and a 5-bar gate from Jacksons Fencing 34 years ago - they are still in very good order with no rot at all.

Therefore, when needing a new fence in a different part of our garden, our decision to choose Jacksons Fencing was our instant choice.

Ronald Broughton, July 2023

Sawn Square Post & Rail Fencing

This sturdy fencing consists of sawn square section posts, with three horizontal rails, nailed to the posts. There is a choice of either half round rails or sawn square section rails.

Allow one post for every 1.80m of fence, plus one for the end of the run. Allow three rails for every 3.60m of 3-rail fencing.

Sawn Square Posts

Length	Ref
1.80m	170100 ●
2.10m	170500 ●
2.40m	170600 ■

125mm x 75mm section, weathered one way. Sawn finish. For corners use ordinary posts.

Square Rails

100mm x 38mm section. Sawn finish.

Length	Ref
3.60m long	170200 ●
4.00m long	170210 ■

For Arenas

Description	Ref
3.60m x 150mm x 38mm Containing Boards	170400 ●
4.00m x 150mm x 38mm Containing Boards	170410 ●
3.60m x 150mm x 25mm Splash Boards	170800 ●
3.60m long x 100mm diameter Jumping Poles (not for in-ground use)	131800 ●
3.60m x 100 x 38mm Square Rails Sawn finish	170200 ●
4m x 100 x 38mm Square Rails Sawn finish	170210 ■

Nails

Description	Ref
1kg Tub of 100mm Galvanised Wire Nails	800310 ●
5kg Tub of 100mm Galvanised Wire Nails	800350 ●

● Stock items ■ Check for availability
○ Made to order (cannot be cancelled once ordered)

Post & Rail Morticed

This attractive fencing consists of sawn square section posts, with three or four horizontal square section rails, morticed into the posts complete with our 25 year guarantee.



There are additional prick posts in between the posts at the mid bay point to give extra support.



Image showing intermediate post in Post & Rail Morticed system

Allow one post and one prick post for every 2.85m of fence, plus one post for the end of the run. Allow three rails per 2.85m run of 3-rail fence, and four rails per 2.85m of 4-rail fence.

All timber used throughout is superior quality Jakcure® treated softwood guaranteed for 25 years. The morticed posts have a galvanised gangnail embedded in the top to reduce splitting of the timber.

All fixings are heavily galvanised.

Posts

125mm x 75mm section, weathered one way. Mortices 100mm x 40mm centred at 150mm, 530mm, 885mm and 1190mm from top of post. Sawn finish.

Length	Ref
1.80m (3 Mortices)	190200 ●
2.10m (4 Mortices)	190700 ○

Square Rails

100mm x 38mm section, scarfed at both ends.

Length	Ref
3.00m	190300 ●



Due to the erratic price changes in raw material, we have temporarily removed prices from our Good Fencing Guide.

To see our latest prices, view our Post & Rail Morticed on our website by scanning the QR code.



Prompt service and excellent product quality. It is perfect for my alpaca paddock. Thank you.

Jan Smith, November 2023

Corner Posts

125mm x 125mm section, weathered two ways. Sawn finish.

Length	Ref
1.80m (3 Mortices)	190600 ●
2.10m (4 Mortices)	190800 ○

Prick Posts

100mm x 38mm section, pointed with a sawn finish.

Length	Ref
1.50m long	190400 ●
1.80m long	190900 ○

Nails

Description	Ref
1kg Tub of 100mm Galvanised Wire Nails	800310 ●
5kg Tub of 100mm Galvanised Wire Nails	800350 ●
25kg Carton of 100mm Galvanised Wire Nails	800300 ●

Allow 11kg for 200m of 3-rail fence and 14kg for 200m of 4-rail fence. Approximately 77 nails per kg.

● Stock items ○ Made to order (cannot be cancelled once ordered)

Chain Mesh Fence

For absolute economy and horse security this fence is highly recommended. It comprises half round vertical posts, machine rounded and pointed. One half round horizontal rail at the top of the fence and galvanised chain link below.



- All timber used throughout is superior quality Jakcure® treated softwood guaranteed for 25 years.
- Specially designed with horse safety in mind.
- Galvanised mesh for longer life.
- Smaller holes in mesh to stop horses' feet becoming caught in wire and causing injuries.
- Superb value.

Allow one post for every 1.8m of fence plus one for the end of the run. Allow one top rail per 3.60m of fence and one 25m roll of 0.90m chain link per 25m run.

Posts

Half round softwood, machine rounded and pointed 125mm across the face.

Length	Ref
1.80m	150110 ●

Half Round Rails

Half round, machine rounded 100mm across face.

Length	Ref
3.60m	135000 ●

Chain Link

50mm mesh conforms to B.S. 1722 Part 1, galvanising conforms to BS EN 10224, wire used is to BS EN 10233. Line wire is supplied with each roll.

Description	Ref
25m roll, height 0.90m, 2.5mm gauge	300100 ●

Corner Posts

Two sawn flat sides from round posts of 125mm diameter.

Length	Ref
1.80m	130550 ●

Staples / Nails

We suggest you use galvanised (barbed) staples 30mm x 3.15mm which would require 3kg. per 200m & 100mm galvanised wire nails 4kg. galvanised ring clips - sufficient for 200m. See page 154.

- Stock items

Fencing Stakes & Posts

This is a versatile and hard wearing general purpose fence suitable for a multitude of agricultural situations. With our Jakcure® treated stakes and galvanised wire it's long lasting too. All timber used throughout is superior quality Jakcure® treated softwood guaranteed for 25 years.



Stakes

Softwood mixed cleft & round 75mm -100mm across or through the butts, peeled, pointed.

Length	Ref

Machine Rounded Fencing Stakes

Pointed, with chamfered tops.

Length	Ref
1.50m long, 75mm diameter	091800 ●
1.65m long, 75mm diameter	091900 ●
1.80m long, 75mm diameter	092000 ●
1.65m long, 90mm diameter	093200 ■
1.80m long, 90mm diameter	093300 ■

Anchor Stakes

Half round with a minimum of 75mm face, peeled to act as a thrust plate for the struts.

Length	Ref

Straining and Corner Posts

Round and peeled. Diameter measurement is approximate through the butt.

Length	Ref

Machine Rounded, with Chamfered Tops

Length	Ref
2.10m long x diameter 150mm pointed	093050 ■
2.40m long x diameter 150mm pointed	093055 ■

Straining Posts and struts should be installed at a maximum of every 50m and at all changes of direction and significant changes of level. Intermediate posts for mild steel fencing at 1.80m centres - suitable for all agricultural applications.

Peeled and Pointed

Length	Ref

Struts

Machine rounded and a minimum diameter of 60mm Jakcure® treated timber.

Length	Ref
1.80m	114900 ■
2.10m	115000 ▲

For Stock (or cattle) Fence

We also supply wire fencing, wire netting, and barbed wire. Staples and galvanised straining eye bolts and tools page 130, 131 and 154 - 158.

- Stock items ■ Check for availability

Wire Fencing & Netting

Ideal for many applications, including protecting small animals, cages, protecting machinery or in some instances may be used as agricultural fencing.



To view our latest prices, visit Wire Fencing and Netting on our website by scanning the QR code.

Hexagonal Wire Netting

Mesh (50m rolls)	Wire Gauge	600mm (H) Ref	900mm (H) Ref	1050mm (H) Ref	1200mm (H) Ref	1800mm (H) Ref
25mm	20	–	193100 ●	–	193300 ●	193400 ●
31mm	19	193900 ●	–	194100 ●	194200 ●	–
31mm	18	–	–	194600 ○	194700 ○	–
50mm	19	195700 ●	195900 ●	–	196000 ●	196200 ●

Suggestions for use: 25mm: plastering and floor screeding; chicken runs. 31mm: protection against the smallest rabbits. 50mm: poultry; general purpose.

Plain Wire (Mild Steel Galvanised)

Size (25kg coils)	Length	Ref
● 5.00mm (6g.)	162m approx.	321000 ■
● 4.00mm (8g.)	254m approx.	321100 ●
● 3.15mm (10g.)	410m approx.	321200 ●
● 2.5mm (12g.)	651m approx.	321300 ●
● 2.0mm (14g.)	1017m approx.	321400 ●
● 1.6mm (16g.)	1590m approx.	321700 ■

Size (5kg coils)	Length	Ref
● 3.15mm (10g.)	82m approx.	323100 ●
● 2.5mm (12g.)	130m approx.	323200 ●
● 2.0mm (14g.)	203m approx.	323300 ●

High Tensile Wire (Galvanised)

Size	Length	Ref
● 3.15mm (10g.)	410m approx.	321500 ●
● 2.5mm (12.5g.)	651m approx.	321550 ●

Barbed Wire (Galvanised)

Our galvanised double strand barbed wire available in 200m with barbs at 100mm centres.

Size	Length	Ref
● 2.5mm	200m approx.	321600 ●
● 1.6mm high tensile	200m approx.	321660 ●



Gripples

Type	Ref
Grippers Wire Tensioning Tool	326900 ●
Grippers Wire Joiner: Ideal for joining both Mild & High Tensile steel wire 1.6mm-3.2mm & High Tensile barbed wire.	326800 ●
Grippers for mild steel barbed wire	326880 ●

● Stock items ■ Check for availability

Galvanised Stock Fencing

(manufactured to BS EN 10223)

- Galvanised wire field fences that are strong, durable & economical
- Wire fencing types 1-4 are coated with Galfan®, highly corrosion resistant zinc and aluminium alloy - Laboratory tests have shown these to last twice as long as ordinary galvanised wires.
- Supplied in 50m as standard or 100m rolls for high tensile.

1 Cattle or Stock Fence (1.15m (Galfan® coated)

Available in medium weight. Eight line wires and uprights 300mm apart.

Type	Wire diameter		Ref
	Top & Bottom	Intermediate	
C8/11/30	3.0mm	2.5mm (50m rolls)	320200 ●

2 Pig Fence (800mm (Galfan® coated)

Eight line wires and uprights 150mm apart (also lamb proof).

Type	Wire diameter		Ref
	Top & Bottom	Intermediate	
Medium C8/80/15	3.0mm	2.5mm (50m rolls)	320400 ●
High Tensile* HT8/80/15	All wires	2.5mm (100m rolls)	320440 ●

3 Sheep Fence (900mm (Galfan® coated)

Six line wires & uprights 300mm apart.

Type	Wire diameter		Ref
	Top & Bottom	Intermediate	
Heavy B6/90/30	4.0mm	3mm (50m rolls)	320700 ●
Medium C6/90/30	3.0mm	2.5mm (50m rolls)	320800 ●

12"			12"			6"		
1	230	9"	3	230	9"	5	260	10.5"
	200	8"		200	8"		220	8.5"
	180	7"		180	7"		220	8.5"
	150	6"		150	6"		200	8"
	140	5.5"		140	5.5"		180	7"
	130	5"		140	5.5"		140	5.5"
	115	4.5"		130	5"		115	4.5"
6"			6"			6"		
2	150	6"	4	230	9"		100	4"
	140	5.5"		200	8"	80	3.25"	
	130	5"		180	7"			
	115	4.5"		150	6"			
	100	4"		140	5.5"			
	90	3.5"		130	5"		80	3.25"
	75	3"						

4 Forest Fence (1.00m (Galfan® coated)

Seven line wires, uprights 150mm apart.

Type	Wire diameter		Ref
	Top & Bottom	Intermediate	
Medium C7/10/15	3.0mm	2.5mm (50m rolls)	325500 ●

5 Deer Fence (1.90m (Galfan® coated)

Vertical wires 150mm apart for perimeter fencing.

Type	Wire diameter		Ref
	Top & Bottom	Intermediate	
High Tensile 13/190/15 (close uprights)	2.5mm	2.5mm (100m rolls)	325600 ●

Tree and Netting Stakes

Jakcure® treated tree stakes are machine rounded in two sizes 60mm and 75 diameter, and are available in lengths of up to 3m. A minimum of 22.3kg/m² of preservative is used because of presence in the soil of fertilizers and dressings used in the modern orchard.

The Jakcure® treatment process meets fruit growers' specifications, and depth of penetration makes the timber last longer, meaning strong stakes that will provide the best support. All timber is Jakcure® treated softwood guaranteed for 25 years.

When its time to overhaul orchards, and replace any rotten or worn tree stakes, replacing them all with Jacksons stakes will mean you will have good strong stakes that will standing for longer, and this means you will save money by not having to replace them as soon as ordinary non Jakcure® stakes, our stakes are guaranteed for 25 years.

Tree and Netting Stakes

*Tree Stakes (pointed and chamfered)

Length	Dia.	Ref
1.50m	60mm	113500 ■
1.80m	60mm	114400 ■
2.10m	60mm	115200 ■
2.10m	75mm	092100 ■
2.40m	60mm	114500 ■
2.40m	75mm	092200 ■
2.70m	75mm	092300 ■

Buckle Tree Ties

Length	Ref
450mm	100900 ●

● Stock items ■ Check for availability



Avoid this happening to your trees

Cleft Chestnut Fencing

A simple, fast and cost-effective demarcation solution, our Cleft Chestnut fencing is assembled using best quality galvanised 14 gauge (2mm) wire with 4 strands per row. Pales are cleft, peeled and pointed at one end.



Please note: this Chestnut fencing is not Jakcure[®] treated timber as Chestnut is a hardwood and therefore cannot be guaranteed for 25 years.



Style A - (2 rows of wire)



Style B - (3 rows of wire)

Approximate spacing: 81 pales in a 9.10m roll. Pales are 75mm spaced. We recommend installation with our machine round Jakcure[®] posts for long life.

Cleft Chestnut Fencing

Fence Height	Ref
0.90m - Style 'A' 9.10m rolls	291000 ●
1.10m - Style 'A' 9.10m rolls	291600 ●
0.90m - Style 'B' 9.10m rolls	294000 ■
1.10m - Style 'B' 9.10m rolls	294600 ●
1.20m - Style 'B' 4.55m rolls	295500 ●
1.40m - Style 'B' 4.55m rolls	295800 ●
1.50m - Style 'B' 4.55m rolls	296400 ●
1.80m - Style 'B' 4.55m rolls	297000 ■

Intermediate Posts (not chestnut)

Machine round, 75mm diameter. Use at 2.70m intervals.

Fence Height	Post Length	Ref
0.90m	1.50m	091800 ■
1.10m	1.50m	091800 ■
1.20m	1.65m	091900 ■
1.40m	1.80m	092000 ■
1.50m	2.10m	092100 ■
1.80m	2.40m	092200 ■

Corner and End Posts (not chestnut)

Machine rounded 100mm diameter. Use at maximum 45m intervals or corners and changes in direction.

Fence Height	Post Length	Ref
0.90m & 1.10m	1.50m	132100 ■
1.20m & 1.40m	1.80m	132200 ■
1.50m	2.10m	132220 ■
1.80m	2.40m	132300 ■



Due to the erratic price changes in raw material, we have temporarily removed prices from our Good Fencing Guide.

To see our latest prices, view Cleft Chestnut fencing on our website by scanning the QR code.



Inspirational

Many thanks to our customers who have shared their projects with us, without these inspirational images it would be difficult for us to show you the many ways that our products can be used.

If you have any photos of our products in your garden projects we'd love to see them, please email: pics@jacksons-fencing.co.uk

Struts (not chestnut)

Machine rounded, 60mm diameter. Use one on end posts and two on corner and intermediate straining posts.

Fence Height	Post Length	Ref
0.90m & 1.10m	1.35m	114700 ▲
1.20m & 1.40m	1.80m	114900 ■
1.50m	2.10m	115000 ▲

Anchor Stakes (not chestnut)

Half round with minimum of 75mm face, pointed and peeled. One per strut 750 - 900mm.

Description	Ref
One per strut 750mm - 900mm	090900 ■

● Stock items ■ Check for availability ▲ While stock lasts

Timber Kissing Gate

A kissing gate is a type of gate which allows the movement of people but not livestock to pass through, keeping them safe and enclosed within an area. This is an alternative to the stile. The term derives from the fact that the gate 'kisses' the stops at the two extremes of its travel.



Timber Kissing Gate

This style of gate has been commonplace in rural areas for years. They are particularly useful in districts populated by older people, where a stile is unsuitable. The kissing gate allows easy access through fences with no climbing necessary.

Specification: The set consists of one 1.05m wide, five bar, Jakcure[®] treated Uni-Field Gate. Hung on galvanised double band hinges with adjustable bottom eye. The hanging post is 2.10m long x 125mm x 100mm section, shaped four ways. The two slam posts are 1.80m long x 125mm x 100mm section. The 'V' shaped enclosure fence has four rails of 100mm x 38mm section morticed into each side of the corner post, which is also 1.80m long x 125mm x 100mm section. All manufactured from Jakcure[®] treated softwood. We recommend that all posts should be set in concrete. This unit is suitable for inserting in any type of fence in almost any situation.

Description

Standard timber Kissing Gate complete set

Ref

299900BM ■

Mobility Timber Kissing Gate (wheelchair friendly)

The Mobility Kissing Gate uses the same materials as the standard Timber Kissing Gate, but with a 1.50m gate, which makes it accessible for wheelchair users. Designed and can be installed in accordance with BS 5709:2006


Description

Mobility timber Kissing gate complete set

Ref

299800BM ■

■ Check for availability



Metal Kissing Gate

Our metal kissing gates provide a solid rigid structure designed to allow the flow of pedestrian access in rural locations such as public footpaths or fields. These gates do not allow livestock to pass through keeping them safe and enclosed within a secure area.



Our Galvanised Metal Kissing Gate

This popular self closing six rail Kissing gate is now available manufactured from hot dip galvanised metal, so it will resist rusting for many years and will be virtually maintenance free once installed.

Specification: Dimensions: 1520mm wide, 1170mm high. Manufactured from 25mm x 25mm RHS with four posts 50 x 50mm RHS including adjustable bottom hinge which allows the gate to swing shut either way. Supplied in three sections plus posts and location bars for below ground. All hot dipped galvanised. We recommend that the posts should be set in concrete. This unit is suitable for inserting in any type of fence in almost any situation.

Please note: this gate has been designed to fit into areas where space is minimal but access is required. It is not recommended for public footpaths as the design is under the minimum clear width of 1.1m, stated in BS5709:2018.

Description

Metal Kissing gate complete set

Ref

264600BM ○

RADAR Padlock

Right of way gates can be secured in the closed position with a padlockable drop bolt, this can be used with a RADAR padlock.

Description

RADAR padlock and three keys

Ref

284550BM ■

■ Check for availability ○ Made to order (cannot be cancelled once ordered)



To see our latest prices, view our Kissing Gates on our website by scanning the QR code.

Rights of Way - Stiles

Jacksons' stiles were designed with walkers and the outdoor enthusiast in mind. No more lifting the dog over and getting covered in mud.



Stile with Dog Gate (Rabbit Proof)

Specification (with dog gate):

Description	Ref
Stile Complete With Dog Gate	201700BM ○
Stile (without dog gate)	200700BM ■
Dog gate for attaching to existing stile	201800BM ○

■ Check for availability ○ Made to order (cannot be cancelled once ordered)



Due to the erratic price changes in raw material, we have temporarily removed prices from our Good Fencing Guide.

To see our latest prices, view Cleft Chestnut fencing on our website by scanning the QR code.



Gate shown with additional chicken wire

Bridle Gates

Description	Ref
Complete Bridle Gate includes 1.8m Uni Gate fitted with hinges, spring catch set, 2 x gate posts	299770BM ■

Two Way R.O.W. Latch

Two way latch especially suitable for self closing gates where disabled people need to gain access.



Description	Ref
Supplied complete with latch timber packer and activating pin.	271100 ■

Demarcation Fencing

Demarcation devices are a type of fencing which is usually a small structure that simply marks a boundary between two areas, and can take many forms to delineate a boundary.



Diamond Rail Fencing

Specification:

Posts	Ref
0.90m long	200900 ■
1.20m long	201000 ■
Rails	Ref
70mm x 70mm 3.60m Rail (posts at 1.80m centres) Heavy duty option - posts can be spaced at 1.20m centres	200936 ●
Galvanised Strap for Diamond Rail	201100 ●

Post and Chain Fencing

Description	Ref
Posts for chain fencing Jakcure® softwood 100mm x 100mm nominal square section, planed shaped top 1.50m	350900 ■
Chain galvanised 50mm x 6mm links spikes in every other link. Price per metre	350600 ●
Hooks galvanised for attaching chain to wooden posts (including screws)	350700 ●

Silver Rail fencing

Specification: Posts are 125mm x 75mm nominal section Jakcure® treated soft wood with rounded tops. Allow 1 post per 2.00m. Rails can be supplied coloured.

Description	Ref
Intermediate Post 1.50m	201200 ■
Corner Posts 1.50m	201300 ○
End Post 1.50m	201500 ■
Rails 6m Galvanised rail (41.5mm diameter including connector)	064000BM ●

● Stock items ■ Check for availability

○ Made to order (cannot be cancelled once ordered)



Silver Rail