

# Woven Panel

# Jacksons Fencing



Part of our premium 'good-both-sides' panels range, Woven is designed with the traditional inter-woven styles of the past in mind. As with all Jacksons panels, they are constructed from Jakcure® treated pressure treated softwood and framed for use with slotted Jakposts®, making them far stronger than traditional versions of this style of fencing.

- All timber used throughout is superior quality Jakcure® treated softwood guaranteed for 25 years.
- All fixings are stainless steel.
- Designed for use with slotted Jakposts®.
- Morticed and tenoned frame for extra strength.
- Part of our premium 'good-both-sides' range.
- Featuring substantial 38mm x 7mm pales that maintain structural integrity.
- Gravel boards are required where panels are in contact with the ground.

## Specification

Panel Heights: 0.91m 1.22m 1.52m 1.83m

Panel Width: 1.83m

Framing: 45 x 51mm section planed.

Pales: 38 x 7mm thickness

Panel Thickness: 51mm

If you need to reduce the width of a panel on site, a cut down kit is available. Always use Jakcure® End Grain Treatment on any cut timber.

## Gates

Gates are Jakcure® treated softwood, right and left hand hanging (when viewed from the outside) and are made to order in standard sizes. They are designed to match our Woven Panel. Non-standard gates with custom width / heights are available as a special order and are also available as pairs (size restriction applies).

- Elegantly designed to match our Woven Panel.
- Galvanised ring latches and adjustable 'L' hinges.
- The gate must only be used with 'L' hinges supplied.
- Wall plates are available for fitting these gates to walls.

Standard Gate Heights: 1.78m (including capping).

Standard Gate Widths: 1m

View our website for Q40 specification documents, CAD drawings and products available to buy online.

A fully made to measure service is available. All Jacksons Fencing systems and gates may be designed and manufactured to suit site conditions.

Note that components can temporarily swell up to 6% in width after our Jakcure® process temporarily affecting the overall product dimensions.

